


Pan-Ty® Cable Ties – Weather Resistant Nylon 12



- For high moisture, corrosive (zinc chloride and dilute acids), and low temperature indoor or outdoor applications
- Cable tie of choice for making attachments to galvanized surfaces
- One-piece construction for consistent performance and reliability
- Among the lowest threading force of any one-piece cable tie in the industry
- Curved tip is easy to pick up from flat surfaces and allows faster initial threading to speed installation




| Part Number | Length | | Width | | Thickness | | Max. Bundle Dia. | | Min. Loop Tensile Str. | | Recommended Installation Tool | Std. Pkg. Qty. | Std. Ctn. Qty. |
|---|--------|-----|-------|-----|-----------|-----|------------------|-----|------------------------|-----|--|----------------|----------------|
| | In. | mm | In. | mm | In. | mm | In. | mm | Lbs. | N | | | |
| Intermediate Cross Section | | | | | | | | | | | | | |
| PLT1.5I-M120 | 5.6 | 142 | 0.142 | 3.6 | 0.045 | 1.1 | 1.38 | 35 | 25 | 111 | GTS-E, GS2B, PTS, PPTS, STS2 | 1000 | 25000 |
| Standard Cross Section | | | | | | | | | | | | | |
| PLT2S-M120 | 7.4 | 188 | 0.190 | 4.8 | 0.052 | 1.3 | 1.88 | 48 | 40 | 178 | GTS-E, GS2B, GTH-E, GS4H, PTS, PTH, PPTS, STS2, STH2 | 1000 | 10000 |
| PLT4S-M120 | 14.5 | 368 | 0.190 | 4.8 | 0.052 | 1.3 | 4.00 | 102 | 40 | 178 | | 1000 | 5000 |
| Light-Heavy Cross Section (Straight Tip) | | | | | | | | | | | | | |
| PLT4H-TL120 | 14.5 | 368 | 0.300 | 7.6 | 0.075 | 1.9 | 4.00 | 102 | 90 | 400 | GTH-E, GTSL, GS4H, GS4EH, PTH, STH2, ST3EH | 250 | 2500 |
| PLT8LH-C120 | 27.6 | 701 | 0.300 | 7.6 | 0.075 | 1.9 | 8.00 | 203 | 90 | 400 | | 100 | 2500 |

Pan-Ty® Cable Ties – Polypropylene – Distinctive Green Color



- For chemical resistance where high loop tensile strength is not required especially in the presence of hydrochloric acid, salts, and bases
- For indoor use
- One-piece construction for consistent performance and reliability
- Among the lowest threading force of any one-piece cable tie in the industry
- Curved tip is easy to pick up from flat surfaces and allows faster initial threading to speed installation



| Part Number | Length | | Width | | Thickness | | Max. Bundle Dia. | | Min. Loop Tensile Str. | | Recommended Installation Tool | Std. Pkg. Qty. | Std. Ctn. Qty. |
|---|--------|-----|-------|-----|-----------|-----|------------------|-----|------------------------|-----|--|----------------|----------------|
| | In. | mm | In. | mm | In. | mm | In. | mm | Lbs. | N | | | |
| Miniature Cross Section | | | | | | | | | | | | | |
| PLT1M-M109 | 3.9 | 99 | 0.098 | 2.5 | 0.043 | 1.1 | 0.87 | 22 | 11 | 49 | GTS-E, GS2B, PTS, PPTS, STS2 | 1000 | 50000 |
| Intermediate Cross Section | | | | | | | | | | | | | |
| PLT1.5I-M109 | 5.6 | 142 | 0.142 | 3.6 | 0.045 | 1.1 | 1.38 | 35 | 18 | 80 | GTS-E, GS2B, PTS, PPTS, STS2 | 1000 | 25000 |
| Standard Cross Section | | | | | | | | | | | | | |
| PLT2S-M109 | 7.4 | 188 | 0.190 | 4.8 | 0.052 | 1.3 | 1.88 | 48 | 30 | 133 | GTS-E, GS2B, GTH-E, GS4H, PTS, PTH, PPTS, STS2, STH2 | 1000 | 10000 |
| PLT3S-M109 | 11.5 | 292 | 0.190 | 4.8 | 0.052 | 1.3 | 3.00 | 76 | 30 | 133 | | 1000 | 10000 |
| PLT4S-M109 | 14.5 | 368 | 0.190 | 4.8 | 0.052 | 1.3 | 4.00 | 102 | 30 | 133 | | 1000 | 5000 |
| Light-Heavy Cross Section (Straight Tip) | | | | | | | | | | | | | |
| PLT2H-TL109 | 8.1 | 206 | 0.300 | 7.6 | 0.075 | 1.9 | 2.00 | 51 | 50 | 222 | GTH-E, GS4H, GS4EH, PTH, STH2, ST3EH | 250 | 2500 |
| PLT3H-TL109 | 11.4 | 290 | 0.300 | 7.6 | 0.075 | 1.9 | 3.00 | 76 | 50 | 222 | | 250 | 2500 |
| PLT4H-TL109 | 14.5 | 368 | 0.300 | 7.6 | 0.075 | 1.9 | 4.00 | 102 | 50 | 222 | | 250 | 2500 |