



"S" selektiv vergoldet bis 33,0mm Stiftlänge.

Art.Nr.	Maße (mm)		Art.Nr.	Maße (mm)	
	A	L		A	L
SL 14 071 ...	7,10	21,40	SL 14 235 ...	23,50	37,80
SL 14 097 ...	9,70	24,00	SL 14 265 ...	26,50	40,80
SL 14 122 ...	12,20	26,50	SL 14 310 ...	31,00	45,30
SL 14 147 ...	14,70	29,00	SL 14 365 ...	36,50	50,80
SL 14 187 ...	18,70	33,00			

... Polzahl "n":
2 - 72

... Oberfläche: S = selektiv vergoldet (6mm)
 G = vergoldet
 Z = verzinkt

Schutzvermerk gemäß
DIN ISO 16016 beachten
© Fischer Elektronik GmbH & Co. KG 2006



Oberfläche
Ni/4-6µm Sn
Ni/0,2µmAu

Kunde 77777 - Fischer Elektronik



Z.	Änderungen	Datum	Name

Datum	Name
Erst. 05.12.2006 Bearb. 24.04.2006	Lochen Lochen
Werkstoff / Material Kontakt: CuSn-Legierung Iso-Körper: PA 4.6	
C001017568.iam	

Bezeichnung / Titel	Blatt
Stiftleiste, SL 14 ... Raster 2,54, 2-72 pol.	1
Zeichnungs-Nummer 001017569	Blätter 1