



Pan-Ty® Releasable Cable Ties – Nylon 6.6

- For indoor use
- Extended release tab permits easy release and re-use where changes are anticipated during development, production, or servicing in the field
- One-piece construction for consistent performance and reliability
- Curved tip is easy to pick up from flat surfaces and allows faster initial threading to speed installation
- UL Listed for use in plenum or air handling spaces per NEC except PRT2H/3H/4H



To release, grasp the head of the cable tie, deflect release tab, and pull the cable tie away from the bundle.



Part Number	Length		Width		Thickness		Max. Bundle Dia.		Min. Loop Tensile Str.		Recommended Installation Tool	Std. Pkg. Qty.	Std. Ctn. Qty.
	In.	mm	In.	mm	In.	mm	In.	mm	Lbs.	N			

Standard Cross Section – Plenum-Rated



UL Type 2S Rated


PRT1S-C	4.8	122	0.190	4.8	0.052	1.3	1.00	25	50	222	Hand install only	100	1000
PRT1.5S-C	6.3	160	0.190	4.8	0.052	1.3	1.50	38	50	222		100	1000
PRT2S-C	7.4	188	0.190	4.8	0.052	1.3	1.88	48	50	222		100	1000
PRT3S-C	11.5	292	0.190	4.8	0.052	1.3	3.00	76	50	222		100	1000
PRT4S-C	14.5	368	0.190	4.8	0.052	1.3	4.00	102	50	222		100	1000

Light-Heavy Cross Section (Straight Tip)

PRT2H-L	8.4	213	0.300	7.6	0.075	1.9	2.00	51	80	356	Hand install only	50	500
PRT3H-L	11.4	290	0.300	7.6	0.075	1.9	3.00	76	80	356		50	500
PRT4H-L	14.5	368	0.300	7.6	0.075	1.9	4.00	102	80	356		50	500

Pan-Ty® Releasable Lashing Ties – Nylon 6.6

- For indoor use
- Release tab permits easy release and re-use where changes are anticipated during development, production, or servicing in the field
- Typically used for heavy duty applications
- Among the strongest Pan-Ty® Cable Tie available
- Can be used with MCEH mounting clip, see page B1.22



Part Number	Length		Width		Thickness		Max. Bundle Dia.		Min. Loop Tensile Str.		Recommended Installation Tool	Std. Pkg. Qty.	Std. Ctn. Qty.
	In.	mm	In.	mm	In.	mm	In.	mm	Lbs.	N			

Extra-Heavy Cross Section

PRT2EH-C	9.0	229	0.500	12.7	0.075	1.9	2.00	51	250	1112	Hand install only	100	1000
PRT5EH-Q	20.1	511	0.500	12.7	0.075	1.9	5.00	127	250	1112		25	250
PRT6EH-Q	22.2	564	0.500	12.7	0.075	1.9	6.00	152	250	1112		25	250
PRT8EH-C	28.3	719	0.500	12.7	0.085	2.2	8.00	203	250	1112		100	1000
PRT10EH-C	34.2	869	0.500	12.7	0.085	2.2	10.00	254	250	1112		100	500
PRT12EH-C	40.1	1019	0.500	12.7	0.085	2.2	12.00	305	250	1112		50	500