


Data sheet Product LA ICK PEN 3 XE

Heatsinks and active heatsinks for processors>Active heatsinks for processors
for Intel Pentium III Xeon

Features

way of fixation:	screw fastening
socket:	Slot 2
thermal resistance:	0.8 K/W
suitable for processor type:	Intel® Pentium® III-Xeon™
dissipation loss:	61.8 W
operating voltage of the fan motor:	12 V
surface:	black anodised
accessories (optional):	<ul style="list-style-type: none"> • alarm exit • molex connection plug

Technical Drawing



Fan**Sepa MFB 50 E 12**

circuit voltage:	10.2...13.8 V DC
bearing type:	ball bearing
fan dimensions:	50x50x10 mm
cur. consumpt.:	50 mA
max. iuitial current:	140 mA
max. volume flow:	238 l/min 14.3 m³/h
max. static pressure:	2.7mm H₂O 26.9 Pa
noise level:	22 dB(A), 1 m lateral
temperature range:	-10°C... +70°C
failure rate (L ₁₀):	95,000 h
MTBF:	280,000 h (20°C)
weight:	19 g
cases:	plastic PBT (UL E54695)

Fischer Elektronik GmbH & Co. KG
DEUTSCHLAND • GERMANY • ALLEMAGNE

Nottebohmstraße 28
58511 Lüdenscheid

Telefon +49 2351 435-0
Telefax +49 2351 45754

info@fischerelektronik.de
www.fischerelektronik.de